



PREMIUM SERIES

9000 VINYL WINDOW SYSTEM

Series 9000 available in horizontal slider, single hung and picture window styles.

- + **Low-E Glass** provides exceptional thermal resistance
- + **Multi-chambered vinyl lineals** improve thermal performance, help retard heat transfer and enhance sound absorbency
- + **3/4" insulated glass** provides energy saving thermal efficiency
- + **3 1/4" frame depth** provides outstanding structural integrity
- + **Beveled exterior frame** provides beauty and elegance
- + **Pre-punched integral nailing-fin** targets proper nail location for quick, easy installation
- + **Frame options** include flush fin and block frame
- + **High-profile nylon fin-seal weather stripping** enhances thermal efficiency
- + **Dual steel-reinforced interlocking meeting rails** provide superior structural integrity and reinforce security latch
- + **Interlocking sashes** help block the infiltration of wind and water
- + **Self-tightening, die-cast cam-action latch and lock assembly** anchored in steel for exceptional security
- + **Equal size glass** in the fixed-lite and sliding vent panel creates an attractive, symmetrical harmony



Series 9000
Horizontal Slider

Single Hung Features

- + **Bottom sash operates and removes** for easy cleaning
- + **Block and tackle balance** offers quiet and smooth sash operation

Slider Features

- + **Self-aligning tandem rollers** glide over a stainless steel track for smooth, effortless operation

CUSTOM Options

- + High Performance Low-E Glass
- + Insulating Argon Gas
- + Optional 1-1/8" triple glaze for superior thermal efficiency
- + Optional acoustical glass packages
- + EZ Action "Positive Action" Lock
- + Continuous head and sill to create twin and triple window units
- + Decorative grids available in Colonial or Perimeter styles; available in 5/8" flat or 1" sculptured
- + Custom sizes available



Series 9000
Single Hung

COLOR Options

- + Standard frame colors include White, Almond or Adobe
- + Inquire about cap stock color options



All products may be ordered to meet Energy Star requirements.

Note: Manufacturer reserves the right to substitute components as necessary for continued product improvement.